



DDH		From	To	Length (m) (1)	Cu %	Ag (g/t)
MS-18-18		12.1	23	10.9	0.14	0.89
MS-18-19		59	104	45	0.31	3.14
	incl. and	61.25 78	68 93	6.75 15	0.56 0.56	6.48 6.31
MS-18-20		10	17	7	0.27	2.61
	and	39	54	15	0.15	0.87
MS-18-21					NSV	NSV
MS-18-22		113	123.2	10.2	0.67	5.19
	and	154	187.8	33.8	0.29	2.28
	incl.	182	187.8	5.8	0.56	6.18
MS-18-23		6.5	14	7.5	0.10	0.63
	and	22	27.25	5.25	0.23	1.31

(1) : True thickness is estimated at 60-85% of the intersected thickness

DDH		From	To	Length (m) (1,2)	Cu %	Ag (g/t)
MS-17-01 ⁽¹⁾		2.90	10.00	7.10	0.44	4.91
MS-17-03 ⁽¹⁾		9.00	129.00	120.00	0.34	2.90
	incl.	21.00	35.50	14.50	0.41	4.73
	and	61.70	129.00	67.30	0.46	3.47
MS-17-04 ⁽¹⁾		3.75	21.10	17.35	0.33	3.63
	and	44.00	175.00	131.00	0.31	2.85
	incl.	48.00	59.00	11.00	0.53	4.81
	and	69.00	88.00	19.00	0.51	6.01
	and	124.80	175.00	50.20	0.40	2.97
MS-17-05 ⁽¹⁾		139.70	169.00	29.30	0.52	3.53
	incl.	92.20	104.00	11.80	0.19	1.54
MS-17-07 ⁽¹⁾		33.40	44.00	10.60	0.13	0.80
	and	91.60	196.00	104.40	0.12	0.85
MS-17-08 ⁽¹⁾		3.90	210.20	206.30	0.18	1.65
	incl.	41.50	97.50	56.00	0.38	3.86
	incl.	42.60	64.50	21.90	0.52	5.62
	and	144.65	179.40	34.75	0.27	2.40
	incl.	144.65	160.80	16.15	0.50	4.30
MS-18-09 ⁽²⁾		138.20	187.00	48.80	0.12	NSV ⁽³⁾
	incl.	163.20	173.50	10.30	0.42	2.02
MS-18-11 ⁽¹⁾		9.00	23.20	14.20	0.22	2.40

(1) : True thickness is estimated at 30-60% of the intersected thickness
 (2) : True thickness is estimated at 75-95% of the intersected thickness
 (3) : NSV = No significant value (<0.1% Cu or <1 g/t Ag)

DDH		From	To	Length (m) (1,2)	Cu %	Ag (g/t)
MS-18-13 ⁽¹⁾		148,90	210,00	61,1	0,30%	2,72
	incl. and	170,00 198,00	183,00 210,00	13,0 12,0	0,47% 0,51%	5,45 4,25
MS-18-14 ⁽¹⁾		18,00	101,00	83,0	0,42%	4,52
	incl.	59,75	94,00	34,25	0,63%	7,45
MS-18-15 ⁽¹⁾		1,55	8,00	6,45	0,28%	4,83
		19,00	56,70	37,7	0,38%	4,47
	incl. and	19,00 46,00	32,00 56,70	13,0 10,7	0,66% 0,49%	8,05 5,65
MS-18-16 ⁽²⁾		19,2	112,0	92,8	0,25%	2,19
	incl.	42,0	66,7	24,7	0,50%	4,97
MS-18-17 ⁽²⁾		17,0	35,0	18,0	0,26%	2,66
		52,0	80,0	28,0	0,49%	5,27
	incl.	52,0	63,0	11,0	0,67%	7,65

(1) : True thickness is estimated at 30-60% of the intersected thickness
 (2) : True thickness is estimated at 75-95% of the intersected thickness

LITHOLOGY

- Calc-silicate unit
- Glimmerite Calcitic marble
- Lesueur Dike
- Paragneiss
- Lithological contact
- Expected lithological contact
- Block (surface sample)

Projection: UTM NAD83 Zone 18

Meters